

Folding-arm awning





Just *enjoy* life!







Family Classic – the classic awning Versatile and practical for patios and outdoor seating areas



Open type

On the basic Family Classic type, the awning fabric roller is exposed ("open"). Round end caps at the sides and the fabric cover shell on the front of the fabric roller lend the awning a harmonious appearance.





A host of extra features

- Width of 1 unit max. 700 cm, joined system max. 1950 cm, drop max. 400 cm
- Supplied as standard with classic valance
- Electric motor
- Options: Radio motor/ radio remote control, automatic weather sensor, LED lighting, radiant heater, support legs, Vario Valance, Lewens-Matik



Lewens-Matik (Option) An additional crank gear mechanism permits smooth adjustment of the awning pitch to adapt it to the position of the sun.

The Family Classic folding arm awning with its typical valance creates a summer-like atmosphere on the patio or balcony. Available in formats up to 700 cm (as a single unit) and up to 1950 cm as a joined system, this awning is perfect even for large areas. A user-friendly awning boasting proven Lewens' quality, the Family Classic can be enhanced by a number of interesting options.

Rain Cover type

The protective cover on the Family Classic Rain Cover type protects the awning against dust, rain and other effects of the weather when retracted.



Encased type

Equipped with a protective cover and back plate, the Encased type of the Family Classic provides secure all-round protection for the fabric roller.

Family Classic

Equipment and technical features



Manufactured and assembled in Germany TÜV-tested safety Quality and technology CE-compliant







Junit (single panel) 700 Cm 700<	Туре	Open	Rain Cover	Encased
unit finite ganet) TOO Cm TOO Cm TOO Cm Lunits finited system with ontinuous owning) 1.200 Cm 1.300 Cm/1.950 Cm	Back bar awning – standard dimensions, retracted (H x D)	182 x 200 mm	178 x 200 mm	178 x 200 mm
1.200 cm - - units/J units (linked system with silt cover) 1.300 cm/1.950 cm 1.300 cm/1.950 cm 1.300 cm/1.950 cm Variation (linked system with silt cover) 1.300 cm/1.950 cm 1.300 cm/1.950 cm 1.300 cm/1.950 cm Variation (linked system with silt cover) 1.300 cm/1.950 cm 1.300 cm/1.950 cm 1.300 cm/1.950 cm Variation (linked system with silt cover) 1.300 cm/1.950 cm 1.300 cm/1.950 cm 1.300 cm/1.950 cm Sipecial arm lengths 1 1 1 1 1 Sipecial arm lengths 1	Unit widths (max.)			
1.300 cm/1.950 cm 1.300 cm/1.950 cm 1.300 cm/1.950 cm Itm lengths 150 / 200 / 250 / 300 / 350 / 400 cm Image: Solution of So	1 unit (single panel)	700 cm	700 cm	700 cm
Drops Arm lengths 150 / 200 / 250 / 300 / 350 / 400 cm Special arm lengths Drive Electric motor (for wall switch) Radio motor Crank drive Crank drive Crank drive Pare colours 19 Lewens standard frame colours 10 Lighting: LED spot bar 11 Radio motor + radio remote control 12 Automatic weather sensor (Sun, wind, rain) 12 Lighting: LED spot bar 13 Radio motor + radio remote control 14 Radio motor + radio remote control 15 Automatic weather sensor (Sun, wind, rain) 16 Radian theater (not with 6, 7, with 3 any wall attachment) 17 Radiant heater (not with 2, 7) 18 Automatic weather sensor (Sun, wind, rain) 19 Lewens-Matik, up to max.600 x 350 cm (mot with 3, 4, 5, 6) 11 Radiant heater (not with 6, 7, with 3, 4, 5, 6) 12 Vario Valance 13 Vario Valance, up to 600 cm wide (not with 3, 4, 5, 6)	2 units (linked system with continuous awning)	1.200 cm	-	-
Arm lengths 150 / 200 / 250 / 300 / 350 / 400 cm	2 units/3 units (linked system with slit cover) 1	.300 cm/1.950 cm	1.300 cm/1.950 cm	1.300 cm/1.950 cm
Special arm lengths I I I I I I I I I I I I I I I I I I I	Drops			
Drive Electric motor (for wall switch) Radio motor I'rank drive I'rank dri	Arm lengths 150 / 200 / 250 / 300 / 350 / 400 cm			
Electric motor (for wall switch) Image: Constraint of the second s	Special arm lengths			
Radio motor Image: Construct of the senser (sum, wind, rain) Image: Construct of the senser (sum, wind, rain) Image: Construct of the senser (sum, wind, rain) Image: Construct of the senser (sum, wind, rain) Image: Construct of the senser (sum, wind, rain) Image: Construct of the senser (sum, wind, rain) Image: Construct of the senser (sum, wind, rain) Image: Construct of the senser (sum, wind, rain) Image: Construct of the senser (sum, wind, rain) Image: Construct of the senser (sum, wind, rain) Image: Construct of the senser (sum, wind, rain) Image: Construct of the senser (sum, wind, rain) Image: Construct of the senser (sum, wind, rain) Image: Construct of the senser (sum, wind, rain) Image: Construct of the senser (sum, wind, rain) Image: Construct of the senser (sum, wind, rain) Image: Construct of the senser (sum, wind, rain) Image: Construct of the senser (sum, wind, rain) Image: Construct of the senser (sum, wind, rain) Image: Construct of the senser (sum, wind, rain) Image: Construct of the senser (sum, wind, rain) Image: Construct of the senser (sum, wind, rain) Image: Construct of the senser (sum, wind, rain) Image: Construct of the senser (sum, wind, rain) Image: Construct of the senser (sum, wind, rain) Image: Construct of the senser (sum, wind, rain) Image: Construct of the senser (sum, wind, rain) Image: Construct of the senser (sum, wind, rain) Image: Construct of the senser (sum, wind, rain) Image: Construct of the senser (sum, wind, rain) Image: Construct of the senser (sum, wind, rain) Image: Construct of the senser (sum, win	Drive			
rank drive	Electric motor (for wall switch)			
Preme colours P3 Lewens standard frame colours Natural silver (E6/EV 1 anodized, small components RAL 9006) Natural silver (E6/EV 1 anodized, small components RAL 9006) Additional RAL, special colours and effect finishes Natural silver (E6/EV 1 anodized, small components RAL 9006) Additional RAL, special colours and effect finishes Natural silver (E6/EV 1 anodized, small components RAL 9006) Additional RAL, special colours and effect finishes Natural silver (E6/EV 1 anodized, small components RAL 9006) Natural silver (E6/EV 1 anodized, small components RAL 9006) Natural silver (E6/EV 1 anodized, small components RAL 9006) Natural silver (E6/EV 1 anodized, small components RAL 9006) Natural silver (E6/EV 1 anodized, small components RAL 9006) Natural silver (E6/EV 1 anodized, small components RAL 9006) Natural service (E6/EV 1 anodized, small components RAL 9006) I reara quality sewing yarn I reara quality sewing yarn I reare quality sewing y	Radio motor			
19 Lewens standard frame colours Natural silver (E6/EV 1 anodized, small components RAL 9006) Additional RAL, special colours and effect finishes Additional RAL, special colours and effect finishes Auvining fabrics, from the LEWENS collection Branded acrylic (spun-dyed, ultra fade resistant) Branded polyester/recycled polyester (spun-dyed, ultra fade resistant)	Crank drive			
Natural silver (E6/EV 1 anodized, small components RAL 9006) Image: Components RAL 9006) Additional RAL, special colours and effect finishes Image: Components RAL 9006) Additional RAL, special colours and effect finishes Image: Components RAL 9006) Additional RAL, special colours and effect finishes Image: Components RAL 9006) Additional RAL, special colours and effect finishes Image: Components RAL 9006) Additional RAL, special colours and effect finishes Image: Components RAL 9006) Additional RAL, special colours and effect finishes Image: Components RAL 9006) Additional RAL, special colours and effect finishes Image: Components RAL 9006) Additional RAL, special colours and effect finishes Image: Components RAL 9006) Branded corylic (spun-dyed, ultra fade resistant) Image: Components RAL 9006) Branded polyester/recycled polyester (spun-dyed, ultra fade resistant) Image: Components Rat 9006) If enara quality sewing yarn Image: Components Rat 9006) Jultrasonic seam welding Image: Components Rat 9006) <	Frame colours			
Additional RAL, special colours and effect finishes Additional RAL, special colours and effect finishes Awning fabrics, from the LEWENS collection Branded polyester/recycled polyester (spun-dyed, ultra fade resistant) Branded polyester/recycled polyester (spun-dyed, ultra fade resistant) Cenara quality sewing yarn Itrasonic seam welding /alance vithout valance out	29 Lewens standard frame colours			
Awning fabrics from the LEWENS collection Branded acrylic (spun-dyed, ultra fade resistant) Branded polyester/recycled polyester (spun-dyed, ultra fade resistant) Grenara quality sewing yarn JItrasonic seam welding JItrasonic seam welding /alance without valance with valance I Radio motor + radio remote control I Radio motor + radio remote control I Lighting: LED spot bar I Radiant heater (not with 6, 7; with 3 only wall attachment) I Support legs (not with 2, 7) I Vario Valance, up to 600 cm wide (not with 3, 4, 5, 6) Attachment Wall	Natural silver (E6/EV 1 anodized, small components RAL 9006)			
Branded acrylic (spun-dyed, ultra fade resistant) Image: Spanded polyester (spun-dyed, ultra fade resistant) Branded polyester/recycled polyester (spun-dyed, ultra fade resistant) Image: Spanded polyester (spun-dyed, ultra fade resistant) Branded polyester/recycled polyester (spun-dyed, ultra fade resistant) Image: Spanded polyester (spun-dyed, ultra fade resistant) Image: Spanded polyester (spun-dyed, ultra fade resistant) Image: Spanded polyester (spun-dyed, ultra fade resistant) Image: Spanded polyester (spun-dyed, ultra fade resistant) Image: Spanded polyester (spun-dyed, ultra fade resistant) Image: Spanded polyester (spun-dyed, ultra fade resistant) Image: Spanded polyester (spun-dyed, ultra fade resistant) Image: Spanded polyester (spun-dyed, ultra fade resistant) Image: Spanded polyester (spun-dyed, ultra fade resistant) Image: Spanded polyester (spun-dyed, ultra fade resistant) Image: Spanded polyester (spun-dyed, ultra fade resistant) Image: Spanded polyester (spun-dyed, ultra fade resistant) Image: Spanded polyester (spun-dyed, ultra fade resistant) Image: Spanded polyester (spun-dyed, ultra fade resistant) Image: Spanded polyester (spun-dyed, resistant) Image: Spanded polyester (spun-dyed, resistant) Image: Spanded polyester (spunded polyester (spu	Additional RAL, special colours and effect finishes			
Branded polyester/recycled polyester (spun-dyed, ultra fade resistant) □ Grenara quality sewing yarn ■ Jltrasonic seam welding □ Jltrasonic seam welding □ Valance - Valance - vith valance - Nation valance - Vith valance - Padio motor + radio remote control - I Adio motor + radio remote control □ I Automatic weather sensor (sun, wind, rain) □ I Lighting: LED spot bar □ I Radiant heater (not with 6, 7; with 3 only wall attachment) □ I Vario Valance, up to 600 cm wide (not with 4, 7) □ I Lewens-Matik, up to max. 600 x 350 cm (not with 3, 4, 5, 6) □ Wall ■	Awning fabrics from the LEWENS collection			
Tenara quality sewing yarn JItrasonic seam welding JItrasonic seam welding /alance /alance without valance without valance I valance I Radio motor + radio remote control I Automatic weather sensor (sun, wind, rain) I Lighting: LED spot bar I Radiant heater (not with 6, 7; with 3 only wall attachment) I Support legs (not with 2, 7) I Vario Valance, up to 600 cm wide (not with 4, 7) I Lewens-Matik, up to max. 600 x 350 cm (not with 3, 4, 5, 6) Wall	Branded acrylic (spun-dyed, ultra fade resistant)			
Jltrasonic seam welding /alance /alance without valance with valance with valance I Radio motor + radio remote control I Radio motor + radio remote control I Automatic weather sensor (sun, wind, rain) I Lighting: LED spot bar I Lighting: LED spot bar I Radiant heater (not with 6, 7; with 3 only wall attachment) I Support legs (not with 2, 7) I Lewens-Matik, up to max. 600 x 350 cm (not with 3, 4, 5, 6) Wall	Branded polyester/recycled polyester (spun-dyed, ultra fade resis	stant) 🗌		
/alance - </td <td>Tenara quality sewing yarn</td> <td></td> <td></td> <td></td>	Tenara quality sewing yarn			
without valance with valance Options I Radio motor + radio remote control I Automatic weather sensor (sun, wind, rain) I Lighting: LED spot bar I Radiant heater (not with 6, 7; with 3 only wall attachment) I Support legs (not with 2, 7) I Vario Valance, up to 600 cm wide (not with 4, 7) I Lewens-Matik, up to max. 600 x 350 cm (not with 3, 4, 5, 6)	Ultrasonic seam welding			
with valanceImage: Construct of the sensor of the sensor (sun, wind, rain)Image: Construct of the sensor (sun, rain)Image: Construct of the sensor	Valance			
Options Radio motor + radio remote control Automatic weather sensor (sun, wind, rain) Lighting: LED spot bar Lighting: LED spot bar Radiant heater (not with 6, 7; with 3 only wall attachment) Radiant heater (not with 6, 7; with 3 only wall attachment) Vario Valance, up to 600 cm wide (not with 4, 7) Lewens-Matik, up to max. 600 x 350 cm (not with 3, 4, 5, 6)	without valance	-	-	-
I Radio motor + radio remote control I Radio motor + radio remote control I Automatic weather sensor (sun, wind, rain) I Lighting: LED spot bar I Lighting: LED spot bar I Radiant heater (not with 6, 7; with 3 only wall attachment) I Radiant heater (not with 6, 7; with 3 only wall attachment) I Support legs (not with 2, 7) I Vario Valance, up to 600 cm wide (not with 4, 7) I Lewens-Matik, up to max. 600 x 350 cm (not with 3, 4, 5, 6) Attachment	with valance			
Automatic weather sensor (sun, wind, rain) I Lighting: LED spot bar I Lighting: LED spot bar I Radiant heater (not with 6, 7; with 3 only wall attachment) I Support legs (not with 2, 7) I Support legs (not with 2, 7) I Vario Valance, up to 600 cm wide (not with 4, 7) I Lewens-Matik, up to max. 600 x 350 cm (not with 3, 4, 5, 6) Attachment	Options			
I Lighting: LED spot bar I I Radiant heater (not with 6, 7; with 3 only wall attachment) I I Radiant heater (not with 6, 7; with 3 only wall attachment) I I Support legs (not with 2, 7) I I Vario Valance, up to 600 cm wide (not with 4, 7) I I Lewens-Matik, up to max. 600 x 350 cm (not with 3, 4, 5, 6) I	1 Radio motor + radio remote control			
I Radiant heater (not with 6, 7; with 3 only wall attachment) I Support legs (not with 2, 7) I Vario Valance, up to 600 cm wide (not with 4, 7) I Lewens-Matik, up to max. 600 x 350 cm (not with 3, 4, 5, 6) Attachment	z Automatic weather sensor (sun, wind, rain)			
Support legs (not with 2, 7) Vario Valance, up to 600 cm wide (not with 4, 7) Lewens-Matik, up to max. 600 x 350 cm (not with 3, 4, 5, 6) Attachment Wall	3 Lighting: LED spot bar			
I Vario Valance, up to 600 cm wide (not with 4, 7) I Lewens-Matik, up to max. 600 x 350 cm (not with 3, 4, 5, 6) Attachment Nall Image: Content of the second sec	4 Radiant heater (not with 6, 7; with 3 only wall attachment)			
I Lewens-Matik, up to max. 600 x 350 cm (not with 3, 4, 5, 6) Attachment Nall Image: Constraint of the second secon	5 Support legs (not with 2, 7)			
Attachment Nall	6 Vario Valance, up to 600 cm wide (not with 4, 7)			
Nall	7 Lewens-Matik, up to max. 600 x 350 cm (not with 3, 4, 5, 6)			
	Attachment			
Ceiling/rafters 🗆 🗆	Wall			
	Ceiling/rafters			

■ Standard □ Option − not available

Possible dimensions and restrictions along with the complete range of electronic accessories can be found in the technical data in the current Lewens price list.



Your stockist will be happy to advise you:



www.lewens-markisen.de